



1300 Series EDi

Diesel engine - Industrial Open Power Unit

1306-E87TA

211 kWm @ 2200 rev/min

The Perkins 1300 EDi Series of variable speed industrial engines is a family of 6 cylinder units with a deserved reputation for providing reliable power and outstanding economy in a wide variety of stationary off-highway applications.

The Perkins 1306-E87T offers a full specification package providing high power and torque from a lightweight compact power unit. Full authority electronic engine management coupled with Hydraulically Actuated Electronic controlled Unit Injectors to provide quiet, clean highly productive power, with outstanding economy.

Productive power

Hydraulically actuated Electronically controlled Unit Injectors - high pressure injection for true through-the-range performance.

Quick-acting, low inertia turbocharger providing forced induction through helical ports for optimum air/fuel mix and complete combustion.

Clean, efficient power

Constant electronic engine monitoring and management enabling precise fuel metering and injection timing for reliable low temperature starting and superb economy with performance.

Electronically optimised fuel air mixing ensures complete combustion, exhaust virtually free of visible smoke and an emissions capability to match current and future off-highway legislation.

Reliable power

Perkins' outstanding reputation comes from our world-class manufacturing capability. Internationally recognised and customer approved quality procedures ensure unsurpassed reliability.

1300 Series EDi engines incorporate some of the most technologically advanced premium features now available in diesel engines.

Designed to fit

Perkins' industrial open power units offer a complete package with matched cooling system for easy installation and ready to run.

Worldwide support

Perkins' network of 4,000 distributors and dealers assures the operator of the highest standards of in-service technical and parts support.

Performance Data		Net Continuous	Speed (rev/min)
Power Output	(kW)	211	2220
Power Output	(bhp)	283	2200
Peak Torque	(Nm)	1458	1600
Peak Torque	(lbf.ft)	1075	1600

1300 Series EDi 1306-E87TA

Standard Power Unit Specification

Mounted air filter
12/24 Volt alternator
12/24 Volt starter
610 mm pusher fan
Radiator and fan guard
Flywheel SAE J620 size 11.5
Flywheel housing SAE2
Hydraulically actuated Electronically controlled Unit Injectors
Engine mounted electronic governor
Oil cooler spin on full flow filters
Wet sump
Turbocharger with exhaust elbow
Front engine mounting foot

Optional Equipment

Timing case PTO
Air filter pre-cleaner
Rear mounting feet
Tool kit
User's handbook and parts manual
Workshop manual

This list is not exhaustive - please consult your Perkins dealer.



General Data

Bore and Stroke	116.6 x 135.9
Number of Cylinders	6 in-line vertical
Cubic Capacity	8.71 litres
Cycle	4 stroke
Aspiration	Turbocharged and air-to-air charge cooled
Combustion System	Direct injection
Compression Ratio	16.9:1
Firing Order	1,5,3,6,2,4
Rotation	Anti-clockwise viewed from flywheel
Governing	Electronic
Cooling	Thermostatically controlled cooling system
Coolant Capacity	37.2 litres
Lubricating Oil Capacity	28.3 litres
Weight (dry)	896.4 kg
Length	1822 mm
Width	913 mm
Height	1369 mm



Perkins Engines Company Limited
Peterborough PE1 5NA
United Kingdom
Telephone +44 (0)1733 583000
Fax +44 (0)1733 582240
www.perkins.com

All information in this leaflet is substantially correct at the time of printing but may be changed subsequently by the Company

